



TM

TECHNICAL DATA

Veedol

Veedol SYNTRON V 0W/20

1 Litre

PRODUCT DESCRIPTION

Veedol SYNTRON V 0W/20 is a fuel efficient C5/C6 engine oil formulated using the very latest additives and base oil technology. This product is suitable for various engine manufacturers requirements for petrol and diesel engine cars both with or without exhaust after treatment devices. SYNTRON V 0W/20 is also used in modern small capacity engines with exhaust gas turbochargers and direct injection.

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C5 & C6
MB: 229.71 & 229.72
STJLR: .51.5122 & .03.5006
Volvo: VCC RBS0-2AE
API: SP & SP RC
BMW: LL-14 FE & LL-17 FE+
Chrysler: MS 12145
Fiat: 9.55535-DSX & 9.55535-GSX
Ford: WSS-M2C947-B1, WSS-M2C962-A1 & WSS-M2C952-A1
ILSAC: GF-6A
Opel: OV0401547

SIZE	PART NO	BARCODE
1 Litre	5624	5020618056249

PRODUCT BENEFITS

*Excellent cold start properties
*Protects engines from LSPI damage

PRODUCT USAGE

Use as recommended by the vehicle manufacturer.



Veedol**Veedol
SYNTRON V
0W/20****1 Litre****DIRECTIONS FOR USE**

As per the vehicle handbook

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place

SHELF LIFE

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	7.8	<9.3	8.52
Cold Cranking Viscosity	ASTM D4684	mPa.s		<6200	5812
Total Base Number	ASTM D2896	mg KOH/g	8		
Pour Point	ASTM D97	°C		-48	
HTHS Viscosity	ASTM D4683	mPa.s	2.8	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			45.452
Density	ASTM D792	@ 15°C			0.845

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

